

2025 Christensen Promotions

All Class General Rules

NO GREY AREA BUILDING!!!

- All drivers must be 16 years of age with a valid driver's license. Those under 18 must have a legal guardian's signature.
- No drugs or alcohol allowed in the pits
- All drivers must wear seat belts, full face helmet and eye protection
- No riders on cars or hot rodding in the pits at anytime
- Driver is responsible for all members of pit crew. Any rules found violated will result in disqualification of driver, crew and car. Forfeiture of any winnings, entry fees and/or trophies will be forced.
- Any mechanical work must be done in pit area only
- No displaying foul/profane language or decoration on vehicle
- Must remove all glass, plastic, mirrors, trailer hitches, chrome, wheel weights, door handles, stock gas tanks and speakers in the rear speaker deck etc.
- Must have a minimum of 2 working brakes
- Must have at least a 15"x15" hole in hood in case of fire
- This will be open hood inspection so have your chains/wire/ bolts ready to take off when you get to inspection

- May weld window net on driver's door (don't get carried away)
- Driver's door may be welded solid using 3"x1/8" steel strap. If you decide to run an outer driver's door safety bar it must be welded no more than 6" forward/rear of the door seams.
- Must have 2 windshield strap/chain/#9 wires. 3"x3/8" strap maximum if using steel. 6" max welded to roof and 6" firewall
- Batteries must be on the passenger floor secured in a METAL box with metal straps to hold down. Limit 2 batteries. No milk crates or ratchet straps will be tolerated. No excuses. Must have a rubber cover over the batteries.
- Gas tank must be mounted in the behind driver's seat or in the middle of the car with a max cage of 24x24 (outside/outside). 15 gallon max. Must be STEEL, STAINLESS STEEL or ALUMINUM. No plastic boat tanks. No ratchet straps to hold to cage. No excuses. If you bolt to floor you must not tie into seat bar. If you mount to rear seat bar it must be at least 4" away from all sheet metal.
- Must have at least a 15"x15" roof sign
- No self tapping screws!!
- IF NOT IN RULES DO NOT ASSUME YOU CAN DO IT!

2025 Christensen Promotions

Mighty Mini (van/suv) Chain stock

- No all wheel drive vehicles. If you have a 4 wheel drive vehicle you must remove 1 driveshaft, no handicap accessible vans.
- 4, 6 or 8 cylinder. MAY V8 SWAP ANY VEHICLE. Lower engine cradles may be used, MUST HAVE OEM RUBBER MOTOR MOUNTS, NO AFTERMARKET MOTOR MOUNTS AND NO WELDING TO MAKE THE MOTOR FIT!
- No moving or switching out transmission crossmembers.
- May run aftermarket pedals, shifter, pinion brake, steering columns, trans cooler and slider drive shafts. No pinion brake protectors.
- May have a 4 point cage with halo. 4x4 max, may have 6x6 mounting plates. Must be welded to sheet metal. Not frame! 1 down bar in the center of the front doors from the cage to the floor will be allowed.
- May weld rearend gears to create posi-track. Rear ends must remain factory to the vehicle. No rearend swaps.
- May run v tread, skid tires. Double stuffed, foam filled is fine. Any rim of choice. Full and small centers are allowed.
- May cut fenders for tire clearance. May have 3- 3/8 bolts/washers holding them together.
- All gas tanks/batteries must be secured and covered inside the vehicle. Despite other derby's letting you run stock gas

tank if it is located in front of the axle. That WILL NOT be allowed at this derby.

- You may fasten hood down in 6 spots using 3/8 chain or 4 loops of #9 wire. If you choose to leave the stock hood mounts in, they will count as 2 of your 6 mounts.
- You may switch out the core support mounts and replace them with 3/4 inch all thread but it cannot be welded in any way. May use as 2 of your 6 hood tie downs as well. All other body mounts must remain factory.
- Any bumper may be used. May stuff and seam weld them. Chrysler v bumpers are fine or if you choose to build a bumper it may be 4"x4" max with a 4" point.
- Bumper brackets may be 4"x6"x1/4" piece of flat steel. Welded on the outside of the frame. Top, bottom, inside frame rail or outside frame rail, you choose. No metal inside of the frame whatsoever. Front bumper height no higher than 25" to the top of the bumper and rear bumper no lower than 20" to the top.
- Driver's door may be welded solid using 3"x3/16" flat steel. All other doors may be welded, chained or wired in 2 places per vertical seam.
- Front suspension may be welded solid with 1- 2"x4"x1/4" flat steel on upper a-arm only. You will be allowed 2 factory/aftermarket leaf spring clamps per side or 2 chains around rearend to the frame, not body. Choose one not both. Non leaf spring vehicles will be allowed 1 loop of

3/8" chain around rear end and around frame, not the body. No swapping suspension.

- Trucks must have full box. Sides may be folded over with no welding. Tailgates must be in upright position. No exposed frame rails whatsoever. Official's decision is final if your vehicle becomes a safety hazard on the track.
- 2-2"x1/4" bars/chains per windshield for safety.
- 8- 4"x6"x1/4" plates may be used for preran vehicles. 4 per frame rail/side. Must have 1" gap between them/ no stacking. Bend must be proven.

Stick to the rules and put on a show!

Any questions call Aaron Christensen 507-476-2285

Good luck to everyone!

2025 Dates

White, SD- Sunday, July 20th @ 3:00 p.m.

Tyler, MN- Sunday, August 3rd @ 3:00 p.m.

Marshall, MN- Saturday, August 16th @ 7:00 p.m.

**Pits/Inspection will open 4hrs prior to each show
PLEASE be early so we can tech & start the show on time!!**